



## RITY10M

10.1" Fanless Full Flat Slim Design Touch Monitor with Full IP-65



- > Realtek 2483AD-CG chip
- > Full Flat Front Panel with Projected Capacitive Touch Supports Multi Touch
- > Optional 5 Wire resistive/ Glass on Top
- > 1 VGA in, 1 HDMI in , 1 USB2.0 (for tuoch function only)
- > Fanless System & VESA 75 x 75
- > Lockable DC Jack connector with +12V DC in
- > OSD Membrane Keypad
- > Front Side IP65 Dust and Water Proof
- > Available in white color with MOQ

### + Spec

System	
<b>System Chipset</b>	Realtek 2483AD-CG
<b>Board</b>	ACC-ADBOARD-02R/03R
I/O	
<b>USB</b>	1 x USB 2.0 (for Touch function only)
Mechanical & Environmental	
<b>Operating Temp</b>	0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temp</b>	-10°C ~ 50°C (14°F ~ 122°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Weight</b>	0.9 Kgs
<b>Dimension (L x W x H)</b>	272 x 178 x 33 mm
<b>Vibration Test</b>	1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
<b>Shock Test</b>	10Grms, IEC 60068-2-27, Half Sine, 11ms
<b>System Fan</b>	Fanless
<b>Construction - Front</b>	Plastic
<b>Construction - Rear</b>	Black
<b>Input Voltage</b>	+12V DC in
Certifications	
<b>Certification Information</b>	CE / FCC Class A
Software Support	
<b>OS Information</b>	Win 7 Win 8 Win 10 Linux
Power Requirement	
<b>Power Connector</b>	Lockable DC Jack
<b>Power Requirement</b>	+12V only
<b>Power Mode</b>	ATX
<b>Adapter</b>	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter)
Panel	
<b>LCD Size</b>	10.1"
<b>Resolution</b>	1024 x 600
<b>Pixel pitch</b>	0.2175 (H) x 0.2088 (V)
<b>Luminance</b>	350 cd/m2
<b>Contrast ratio</b>	500
<b>Viewing angle</b>	70 (U), 70 (D), 70 (L), 70 ( R)
<b>Response time</b>	16ms
<b>Backlight</b>	LED
<b>Touch Type</b>	Projective Capacitive
<b>Touch Light Transmission</b>	86%
<b>Touch Controller</b>	USB touch (EETI)

### + Ordering

RITY10M-0CV0HUS00R  
10.1" PCAP Monitor/Black/VGA/HDMI/USB/OSD membrane/12V adapter/VESA75x75