LPC-P185W-10

18.5" P-cap Panel PC with Celeron® N3160, IP65 / 66 Bezel-Free and Wide Range Power Input



Full HD

Features

- Celeron® N3160 Quad Core 1.6GHz
- IP65 / 66 Front Panel
- Bezel-Free Design
- 18.5" P-cap Flat Bezel
- Fanless Design
- 3-Pin Power Input Terminal Block
- DC 9~36V Wide Range Power Input
- 1920*1080 Resolution
- 350 nits LED Backlight
- 1000 nits LED Backlight (Optional)
- Lockable HDD Tray

Specification

System	
Processor	Intel® Celeron® N3160 SoC CPU
System Memory	DDR3L SO-DIMM, up to 8 GB
External I/O Port	4 x USB 3.0 2 x GbE LAN (RTL8111G) 1 x Display Port 1 x HDMI 3 x RS-232 1 x RS-422/485 (COM1) 1 x Audio 1 x Power press button 1 x 3-Pin Power Input 1 x Lockable HDD Tray
Storage	1 x SATA3 (6.0Gb/s) 1 x mSATA (full size mini-PCIe)
Operating System	Windows 7 Pro, Windows Embedded Standard 7, Windows 8, Windows 10
Expansion	2 x MiniPCIe Slot

Power Requirement	
Power Type	3-Pin Power Input Terminal Block DC 9~36V Wide Range Power Input

Touch Screen	
Type	18.5" P-cap USB

LCD	
Display Type	18.5" TFT-LCD
Max. Resolution	1920*1080
Max. Color	16.7 M
Luminance	350 nits
View Angle	89/89/89/89
Backlight Lifetime	30,000 hours

Mechanical	
Construction	Metal
IP Rating	Front Panel IP65 Front Panel IP66 Compliant
Mounting	VESA / Panel Mount
Dimension	TBC

Environment	
Operating Temp	-20~60 °C IEC-60068-2-1/2/14
Storage Temp	-20~70 °C
Humidity	10~90% @40 °C, non-condensing
EMC	FCC / CE Class A Certification CE Class B Compliant
Vibration	1.5 Grms @10~500Hz, IEC-60068-2-64

Russia: LLC “ID Solution”, +7 495 545 3283, www.idsolution.ru

Dimension & I/O Connector



Ordering Information

LPC-185W-10	18.5" P-cap Panel PC, Celeron® N3160,1920 x 1080 Reso, 350 nits, 4 COM, 4 USB, 2 LAN, DC 9~36V Power Input, including a 3-Pin Power Adapter (12V/7.5A)
WFK-024	WiFi kits w/ cable & Antenna (2.4GHz, 802.11 b/g/n, 1T1R)
WFK-524	WiFi kits w/ cable & Antenna (2.4 & 5GHz, 802.11 a/b/g/n/ac + BT, 2T2R)
04-US-26-00002	120 W / 24V power adapter with 3 pin terminal block (For High Brightness Model)

Ordering Code

LPC-P185W-10	-H / -OB / -G / -AG / -AR / -B / -V / -T
H = High Brightness 1000 nits LED backlight	
OB = Optical Bonding	
G = Glass withtout touch	
AG = Anti-Glare	
AR = Anti-Reflection	
B = Power Board for Input on board fuse / Input reverse protection / Over current protection / Output short circuit protection	
V = Vandal Proof Glass (By Project)	
T = Operating Temperature -20~60°C	

Russia: LLC “ID Solution”, +7 495 545 3283, www.idsolution.ru