

# TOF-150S

15" touch open frame with VGA/DVI, panel mounting kits, 3-pin terminal block DC 12V adapter



## Features

- ▶ VGA / DVI Port
- ▶ Panel Mounting Kits
- ▶ Optional DC 9~36V Power Input
- ▶ Optional 1000 nits High Brightness
- ▶ Optional Optical Bonding Service



## Specification

LCD		Power Requirement	
Max. Resolution	1024 x 768	Power Input	DC 12V adapter with 3-Pin Terminal Block Optional DC 9~36V Wide Range Power
Contrast Ratio	500 : 1	Mounting	Panel Mount VESA Mount 75x75
Max. Color	16.2M	Operating Temp	0~50 °C
Luminance (cd/m2)	250 nits		
View Angle	120 / 140		
Touch Screen	USB Resistive		

## Ordering Information

TOF-150S	15" touch open frame with VGA/DVI, panel mounting kits, 3-pin terminal block DC 12V adapter
TOF-150SH	15" touch open frame with 1000 nits brightness, VGA/DVI, panel mounting kits, 3-pin terminal block DC 12V adapter
TOF-150SB	15" touch open frame with VGA/DVI, panel mounting kits, DC 9~36V wide range power input
TOF-150SOCA (By Project)	15" touch open frame with optical bonding, VGA/DVI, panel mounting kits, 3-pin terminal block DC 12V adapter

\* All specifications are subject to change without prior notice.



## Dimension

