




MB-i89Q0

6th Generation Intel® Core™ Processor Embedded Micro-ATX Motherboard



Features

- Supports Intel® LGA1151 6th Gen. Core Processors
- Integrated Dual Gigabit Ethernet
- DVI-I and DisplayPort Port supported
- DDR4 Non-ECC Long-DIMM supported
- SATA RAID 0, 1, 5, 10 supported
- Max. three independent displays
- Anti-Crash Technology for automatical system BIOS recovering

System

CPU	Supports 6 th Generation Intel® Core™ i7/i5/i3 processors in LGA1151 socket
Memory	4 x 288-pin DDR4 Long-DIMM sockets, supporting 2133/1866MHz SDRAM up to 64GB
Chipset	Intel® PCH Q170
BIOS	AMI UEFI ROM
TPM	Supports TPM 1.2 & 2.0 daughterboard via LPC connector (optional)
Watchdog Timer	1~255 levels reset

I/O

Super IO Chipset	FINTEK F81768 FINTEK F81216AD (OEM request)
Serial Port	2 x RS-232 ports, up to 4 x RS-232 ports (OEM request)
USB Port	10 x USB 2.0 ports 4 x USB 3.0/2.0 ports
Keyboard & Mouse	6-pin wafer connector for PS/2 keyboard/ mouse via Y-cable
Expansion Bus	1 x PCI slot 1 x PCIe16 Gen 3.0 slot 1 x PCIe4 in x8 slot 1 x PCIe1 slot
Storage	Six Serial ATA ports with 600MB/s HDD transfer rate RAID 0, 1, 5, 10 supported
Ethernet Chipset	1 x Intel® i210AT PCIe GbE controller 1 x Intel® i219LM PCIe GbE PHY
Audio Interface	Realtek® ALC269 5.1 Channel HD Audio CODEC, Mic-in/ Line-in/ Line-out with Amplifier

Display

Graphic Chipset	Integrated Intel® HD Graphics 5x0
Graphic Interface	1 x DVI-I port 2 x DisplayPort ports



Recommended CPU List:

Intel® Core™ i7-6700 quad-core 3.4 GHz processor
Intel® Core™ i5-6500 quad-core 3.6 GHz processor
Intel® Core™ i3-6100 dual-core 3.7 GHz processor

Mechanical & Environmental

Power Requirement	24-pin + 4-pin ATX power connector
Power Consumption	2.34A @+12V with i3-6100 (Typical) 3.83A @+12V with i7-6700 (Typical)
Operating Temp.	0 ~ 60°C (32 ~ 140°F)
Operating Humidity	10 ~ 95% @ 60°C (non-condensing)
Dimension (L x W)	244 x 244 mm (9.6" x 9.6")


Dimensions



Unit:mm



Block Diagram



Ordering Information

MB-i89Q0	Socket LGA1151/ PCH Q170 for Intel® 6 th Gen. processor micro-ATX motherboard
CPF-67Q0-C1	CPU COOLING FAN FOR LGA1151

Optional Accessories

SCDB-3291	TPM 1.2 Daughter board with Infineon OPTIGA TPM SLB9660
SCDB-3292	TPM 2.0 Daughter board with Infineon OPTIGA TPM SLB9665
CBK-11-89Q0-00	Cable kit 2 x USB 2.0 cable w/ bracket (2 ports / cable) 1 x COM port cable 6 x SATA cables 2 x DP cables