



Technical Specification



Smart Beacon Two







Locatify

High performance to solve your problems

- Independently rated "highest performance" beacons.
- Trusted by 15,000+ clients

Smart software saves you money

- instead of months
- Complete API & SDK gets you developing quickly

Enterprise ready to support your business

- Shipping up to 10,000 beacons worldwide in just 5 days
- locations to simplify your logistics

Completely secure to keep your business safe

- Firmware lock keeps your beacon data safe no matter what

Tailored to represent your business

- Customize the logo & color to represent your business















	Dimensions and weight	Height	15 mm (0.59 in)
General	Difficusions and weight	Width	55 mm (2.16 in)
		Depth	56 mm (2.16 in)
		Weight	38 grams (1.30 oz)
	Casing	Material	LUPOY GN5001RFG
		Flame resistance	Safe - V0 flammability class
		Water resistance	Up to 1 meter
		Protection	IP-57 (dust protected and waterproofed for up to 1 meter)
		Colors	White, Black
		Custom color	Min order size - 200 units
		Custom logo	Min order size - 100 units
		Openable	Yes. With tools
	Profiles	iBeacon	Yes
		Eddystone	Yes
	Power Supply	Battery type	2 x 1,000 mAh CR2477 cell
		Battery life	Up to 4 years with default settings and 24-hours daily usage
		Battery replacement	Yes
	Mounting method		Screws; Tape
Components Support/ Management	Processors	Main	32-bit ARM® Cortex™ M0 CPU core
		Bluetooth	Nordic nRF51822
		Data rates	250 kBs, 1 Mbs, and 2 Mbs
		Memory	256 KB flash 16 KB RAM
	Communications	Bluetooth	Bluetooth Low Energy wireless technology 2.4GHz RF
		Transmission power	-30 dBm to 4 dBm
		Sensitivity	-93 dBm
	Range		1 meters - 60 meters
	Sensors		No
	Security	Anti-Hacking	Yes, Kontakt.io Secure Communication
	·	Anti-Cloning	Yes, Kontakt.io Secure Shuffling
		Anti-PiggyBacking	Yes, Kontakt.io Secure Shuffling
		Anti-Cracking	Yes, Software Lock
	Management	Advertising packet configuration	Yes. Proximity UUID, major, minor (iBeacon); Namespace ID, Instance ID, URL (Eddystone); Interval
		Battery level monitoring	via Android and iOS SDK
		Remote fleet management	via Android and iOS SDK
	Platform support	iOS SDK	Yes, v. 8.0 or higer
		Android SDK	Yes, v. 4.3 or higher
		API	Yes
		Web Panel	Yes, Android and iOS
Operations	Environmental	Temperature	-20°C / + 60°C (-4°F / +140°F)
	Requirements	Humidity	from 0% up to 100%
	Certificates		CE - European Union FCC - Unated States Radio Law Certification - Japan Anatel - Brazil KCC - Korea
	Lead time	3 - 10 000 beacons	2-5 business days
		10 000+	Call Us
	Mannente		Lifetime
the state of the s	Warranty		

Get in touch



- ≼ kontakt@kontakt.io
- f facebook.com/kontakt.io
- @kontakt.io
- . +48 123 793 445
- Montakt.io
 Stoczniowców 3, 30-709
 Kraków, Poland



